



HP Color LaserJet 4700 series printer and CM4730 MFP Series

4700n • 4700dn • 4700dtn • 4700ph+ CM4730 • CM4730f • CM4730fsk • CM4730fm



Print office documents and marketing material in brilliant color with crisp detail on a range of papers. Watch productivity soar with print, copy, scan, and fax' functions integrated into one reliable device.

Brilliant color out of the box

Get more done. Print color and black-and-white documents at speeds up to 31 pages per minute (ppm) with the HP Color LaserJet 4700 series printer, and up to 30 ppm with the HP Color LaserJet CM4730 MFP series. Packed with power, this MFP series is a complete office solution—with print, fax, copy, and send-to functionality.^{1,2}

Realize the advantages of color—For professional results and brilliant color every time, count on HP ColorSphere toner and ImageREt 3600. The reliable, all-in-one design of Original HP Color LaserJet print cartridges provides you with trouble-free printing, page after page, cartridge after cartridge. HP's color access controls help you protect your investment, while still reaping the benefits of color when you need it. Control who has access to color printing capabilities and monitor color printing.



- 1 Standard and available features vary according to model. See "Technical Specifications" on page 6 for more details.
- 2 HP Digital Sending Software 4 is optional (not included, sold separately). Software is server-based, server required. Trial is included.





Easy for IT and end users

- Enjoy best-in-class HP Jetdirect embedded networking.
 Transfer information quickly and reliably for increased
 efficiency. HP Web Jetadmin offers remote installation,
 configuration and proactive management—including
 color control. The HP Embedded Web Server performs
 remote diagnostics, sends e-mail alerts, provides job
 tracking and accounting, and automates supplies
 ordering.
- Let the device work for you. HP Smart Printing
 Technology³ works with the device and HP print
 cartridges to make automatic adjustments for reliable,
 consistent results every time you print. Simply and
 conveniently replace cartridges with HP SureSupply™
 shopping and online ordering.⁴
- Easy to use—Your time is precious, so you want an effortless printing experience. The HP Color LaserJet CM4730 MFP's award-winning HP Easy Select Control Panel redefines usability.⁵

Expandable functionality

- Take a break from reloading paper. The HP Color LaserJet 4700 series printer offers an amazing input capacity of up to 2,600 sheets, and the HP Color LaserJet CM4730 MFP series handles your busy workgroup with an input capacity of up to 1,600 sheets. Both products feature a 100-sheet multipurpose tray and 500-sheet input trays.¹
- Effortlessly deliver finished output. You'll save time with scalable finishing features. Add the stapler/stacker with job offset to the HP Color LaserJet 4700 series printer to staple your documents or separate print jobs for easy retrieval. For the HP Color LaserJet CM4730 MFP series, choose the 500-sheet stapler/stacker to staple up to 30 pages or the 700-sheet 3-bin mailbox to assign print, copy, and fax output to different mailboxes or assign users to each tray.¹
- Boost productivity with a multifunction product.¹ The HP Color LaserJet CM4730 MFP series delivers the same great printer capabilities as the HP Color LaserJet 4700 series printer, plus offers your workgroup easy, high quality two-sided scanning, copying, and fax via the Automatic Document Feeder (ADF).

Preserves your budget

• Designed for the way you work—This MFP series delivers the office functions you perform 96% of the time—letter and legal-sized printing. While tabloid printing and copycentric features are nice to have, are they worth the extra expense? Avoid the up to 65% higher purchase prices of comparable digital devices and the up to 36% higher total cost per page. When you're looking for an MFP that truly fits your usage needs, consider a purchase that makes the most financial sense—relevant functionality at a price that makes sense.

Vivid color and powerful performance

If you want brilliant print quality that exceeds your expectations every time you print, but you don't want to make a lot of adjustments or sacrifice fast printing speed and flexible features, these devices are for you. For vibrant color documents and expandable paper-handling capabilities, choose the HP Color LaserJet 4700 series printer with an input capacity of up to 2,600 sheets as well as finished output with the optional 750-sheet stapler/stacker with job offset.1 The HP Color LaserJet CM4730 MFP series expands on the performance and output quality of the HP Color LaserJet 4700 series printer by offering the ability to copy, scan, fax and digitally send documents to e-mail or network folder. (You cannot upgrade the printer to include these features.) The MFP also offers a standard input capacity of up to 1,600 sheets and a choice of paper handling output solutions with the 700-sheet, 3-bin mailbox or the 500-sheet, stapler/stacker.1

- 3 Using genuine HP supplies ensures availability of all HP printing features.
- 4 To learn more about HP SureSupply™, visit www.hp.com/go/SureSupply.
 5 Buyer's Lab gave HP a "Pick of the Year" award in December 2006 for "Outstanding Achievement for the User Interface Design of its Multifunction Printers."
- 6 Purchase figure is based on cost comparisons with comparable workgroup-class digital devices available as of June 2006. Total Cost Per Page (TCPP) figure based on short- and long-life consumables, hardware, and service at 6,000 pages/month: color TCPP quoted, mono (black) has a 20% cost advantage.
- 7 Source: Proprietary study of general office paper use worldwide, Lyra Research Inc.

Get the best-in-class color laser solution that meets your workgroup's demanding performance and print quality needs.

In-house color marketing

Print short-run color documents in-house, quickly and affordably. When you print materials in-house, you have control over the process: you ensure that printing is effective, efficient, and affordable, and that any private company information stays safe. Printing frequently updated materials on-demand, such as promotional material or brochures, means that you can make changes at a moment's notice and never waste printed material due to obsolete information. You also save the time and cost of inventory management. Companies ranging from small to large report that HP's affordable, best-in-class color solutions deliver money to their bottom line. Some ways, such as improving your image and adding impact to marketing publications, are indirect. Others are direct and measurable, such as productivity gains and tangible cost savings with in-house color printing.

HP ColorSphere toner

With HP ColorSphere toner, your prints will shine with uniform gloss and a dynamic range of color. The toner features gloss levels that are significantly improved over previous HP color toners when printing on glossy paper. Improved melting and fusing technologies work in sync with the toner to enable superior toner release and flow. The result is brilliant, intense colors and excellent photo quality output for your business documents.

HP's color toner enables a finer range of colors because each toner particle conforms to an extremely consistent size and shape. This consistency allows particles to be placed on the page with the precision needed to produce a wide range of colors with the most subtle differences in shading. HP ColorSphere toner is also designed to enable faster printing time. The toner particles are chemically grown around an optimally-sized wax core, producing particle sizes that are designed to work with HP's fusing technology for faster printing without sacrificing quality.

Intelligent printing

Designed with office workgroups in mind, the product is simple to install, use and maintain.

 Integrate documents into workflows with the HP Color LaserJet CM4730 MFP series. Optional HP Digital Sending Software facilitates document workflow and enhances business communications by enabling Optical Character Recognition (OCR), and sending to shared network folders and fax services, including LAN fax, Internet fax, and Windows® fax services.

- HP completely redefines the term usability with the HP Color LaserJet CM4730 MFP's radically simple, award-winning HP Easy Select Control Panel. Take advantage of your MFP's complete feature set with an intuitive interface that clearly displays all available applications. The HP Color LaserJet 4700 series printer control panel offers complete, timely information about the printer and print jobs. Designed for quick and easy troubleshooting, the control panel displays up to four lines of text and animated graphics simultaneously.
- An always-on, internal clock improves product availability for both the HP Color LaserJet CM4730 MFP series and HP Color LaserJet 4700 series printer. Once configured, the product can be configured to automatically wake up from sleep mode so that it is ready to work when you are.

HP color management tools

The HP color access control solution makes color printing and copying more affordable than ever by helping you control who uses color and when they use it:

- Control color copying. Color copy lockout allows IT administrators to password-protect the HP Color LaserJet CM4730 MFP series as a black-and-white only copier, so you can control when and how color is used in your workgroup.
- Assign color access to specific users or workgroups.
 Use either your printer's embedded Web server or HP
 Web Jetadmin's fleet configuration capability to
 designate who has access to color printing. That way,
 people who truly need color—such as your sales team
 and marketing department—can use it.
- Assign color access by application. Designate
 certain applications for printing color and others for
 printing black-and-white to ensure that users only
 print color on their most important print jobs and
 that other printouts—such as Web pages—are always
 black-and-white.
- Shut down color completely or temporarily disable color capability. Disable color printing on shared printers—locking out all individuals and workgroups—so you can save your color resources for special projects or seasonal needs. IT administrators can set print settings to control color printing using HP Web Jetadmin's Print Driver Pre-configuration Plug-in.
- Track color use by job, by user, and by device. HP Web
 Jetadmin's Report Generation Plug-in generates real-time
 and periodic usage reports that make it easy to track
 color use by job, by user, and by device. Plus, it allows
 you to easily allocate costs to individual departments.8

⁸ Billing solutions are an optional feature available at an additional cost through HP's solution partners.

HP Color LaserJet 4700 series printer

- 1 750-sheet stapler/stacker with job offset staples up to 30 sheets for instant reports or presentations
- 2 Automatic two-sided printing at full engine speed
- 3 100-sheet multipurpose tray handles heavy custom media up to 58lb bond (220g/m²)
- Five universal 500-sheet input trays support paper up to 32lb bond (120g/m²)
- 5 Control panel simultaneously displays up to four lines of text and animated graphics
- 6 Front door allows convenient access to all four HP print cartridges and supplies seven 40GB HP high-performance embedded hard disk
- 8 544MB total memory quickly and easily handles complex print jobs
- 9 Hi-Speed USB 2.0 port
- 10 Host USB accessory port
- 11 Bidirectional IEEE-1284-C parallel port
- 12 HP Jetdirect Fast Ethernet embedded print server
- 13 Two open EIO slots





HP Color Laserjet 4700ph+ printer shown

Series at a glance



HP Color LaserJet 4700n Printer (Q7492A)

- 100-sheet multipurpose tray and 500-sheet input tray 2 for a 600-sheet capacity
- 500-sheet output bin
- 128MB RAM
- One empty DIMM slot and two empty flash memory slots
- HP Jetdirect Fast Ethernet embedded print server
- Two open EIO slots



HP Color LaserJet 4700dn Printer (Q7493A)

HP Color LaserJet 4700n plus:

- Additional 128MB RAM for 256MB total memory
- · Automatic two-sided printing



HP Color LaserJet 4700dtn Printer (Q7494A)

HP Color LaserJet 4700n plus:

- Two additional 500-sheet input trays for a 1,600-sheet capacity
- Additional 128MB RAM for 256MB total memory
- Automatic two-sided printing
- Printer stand



HP Color LaserJet 4700ph+ Printer (Q7495A)

HP Color LaserJet 4700n plus:

- Four additional 500-sheet input trays for a 2,600-sheet capacity
- 750-sheet stapler/stacker with job offset in place of the 500-sheet output bin
- 40GB HP high-performance embedded hard disk
- Additional 384MB RAM for 512MB total memory
- Automatic two-sided printing
- Printer stand

HP Color LaserJet CM4730 MFP series

- 1 50-sheet ADF scanner processes two-sided documents at full speed
- 2 HP Easy Select Control Panel provides effortless interaction with the MFP
- 100-sheet multipurpose tray handles heavy custom media up to 58lb bond (220g/m²)
- 4 Side door allows convenient access to four, all-in-one HP print cartridges five 700-sheet, 3-bin mailbox allows you to sort by user, print, copy, or fax jobs
- 6 Full-speed, automatic two-sided printing
- 7 Three adjustable 500-sheet input trays support paper up to 32lb bond (120g/m²)
- 8 Foreign interface harness for third-party paper-handling solutions
- 9 Hi-Speed USB 2.0 ports
- 10 IEEE-1284-C parallel port
- 11 HP Jetdirect Fast Ethernet embedded print server
- 12 RJ-11 fax port
- 13 One open EIO slot to add even more functionality, including Apple networking
- 14 448MB total memory quickly and easily handles complex print jobs
- 15 40GB HP high-performance embedded hard disk





HP Color Laserjet CM4730fm MFP printer shown

Series at a glance









	CM4730	CM4730f	CM4730fsk	CM4730fm
100-sheet multipurpose tray		•	•	٧
Three 500-sheet input trays	•	•	•	•
500-sheet output bin	•	•	not available	not available
Memory	448MB	448MB	448MB	448MB
HP Jetdirect Fast Ethernet print server	•	•	•	•
Built-in automatic two-sided printing	•	•	•	•
40GB high performance hard drive	•	•	•	•
HP LaserJet MFP Analog Fax Accessory 300	optional	•	•	•
500-sheet stapler stacker	optional	optional	•	not available
700-sheet, 3-bin mailbox	optional	optional	optional	•

Technical specifications

	4700n (Q7492A)	4700dn (Q7493A)	4700dtn (Q7494A)	4700ph+ (Q7495A)	CM4730 MFP (CB480A)	CM4730f MFP (CB481A)	CM4730fsk MFP (CB482A)	CM4730fm MFP (CB483A)	
Print and copy speed*		Up to 31 ppm				Up to 31 ppm, letter (color and black-and-white); Up to 30 ppm, legal (black-and-white)			
First page out, printing	Less than 1	10 seconds letter, Ready; le	ss than 16.5 seconds letter,	PowerSave		onds letter, Ready;		onds letter, Ready;	
Date and the second second				400 v 400 da: vidi		nds letter, PowerSave	less than 25 secon	ds letter, PowerSave	
Print resolution Features				600 x 600 dpi, witi	h HP ImageREt 3600				
Copying		Not a	vailable		Up to 999 copies: red	uce or enlarge from 25 to 4	100% (from scanner alass)	25 to 200% (from ADE)	
Faxing			Not available Up to 999 copies; reduce or enlarge from 25 to 400% (from scanner glass), 25 to 200% Not available Optional via fax Fax speed: up to 33.6 kbps; JBIG compression, fax forwarding						
		Not distillable			accessory broadcasting to up to 100 locations, speed dial (up to 100 numbers), auto fa reduction, and auto dialing is supported				
Scanning		Not available			Color flatbed scanner or ADF; up to 600 x 600 dpi 30-bit (flatbed), up to 600 x 300 dpi 30-bit (ADF) scan input modes: copy, e-mail, fax, secondary e-mail, folder, workflow				
Digital sending	Not available				Via optional HP Digital Sending Software: secondary e-mail, send-to-folder, send-to-workflow, authentication, digital fax (send-to-LAN, Windows* 2000, Internet); formats: PDF, JPEG, TIFF, MTIFF				
Processor Memory, standard	160MB total	2001	B total	544MB total	Hz RISC	440MD, 204MD DAM	and 64MB fixed memory		
Available memory slots			ry and two available flash :		Evpandable via 256 [DIMMS, two available flash	,	or third party solutions	
Transport memory store	anpanadate na dite and		party solutions		2.100.000.000.000.000	,		о ран, сольно	
Memory, maximum		544M	B RAM			512M	B RAM		
Hard disk	Optional 2	OGB HP high-performance	via EIO slot			40GB HP high-performance	e		
Maximum monthly duty cycle ¹⁰			0 pages				0 pages		
Recommended monthly volume ¹¹		3,000 to 10),000 pages			5,000 to 9	,000 pages		
Media Paper handling	100-sheet multipurpose for a total o		100-sheet multipurpose tray, 500-sheet trays 2, 3, 4 for a total of 1,600 sheets	100-sheet multipurpose tray, 500-sheet trays 2, 3, 4, 5, 6 for a total of 2,600 sheets	50-sheet ADF			of 1,600 sheets	
Two-sided printing	Manual		1,000 3110013		lard automatic two-sided pr	inting			
Output	50	00-sheet face-down output l	bin	750-sheet stapler/		down output bin	500-sheet	700-sheet 3-bin mailb	
·		· .		stacker with job offset		·	stapler/stacker		
Sizes	executive, envelopes 8.5 x 14" (216 x 356 m	(No. 10, commercial); 500 nm); letter, legal, executive;	5 x 14" (216 x 356 mm); le 0-sheet input trays: 5.8 x 8.5 custom sizes not supported tapling with the optional sta	3" (148 x 210 mm) to I for automatic two-sided	Multipurpose tray: 3 x 5" (76 x 127 mm) to 8.5 x 14" (216 x 356 mm); letter, legal, executive, 16k, envelopes (No. 10, commercial.); 500-sheet input trays: 5.8 x 8.3" (148 x 210 mm) to 8.5 x 14" (216 by 356 mm); letter, legal, executive, custom sizes not supported for automatic two-siprinting, optional 3-bin mailbox, and stapling with the optional stapler/stacker				
Weights			; Automatic two-sided print stapler/stacker: 16 to 32lb						
Types	Paper (plain, p	reprinted, letterhead, prep	unched, bond, recycled, co	lor, light, intermediate, heav	y, extra heavy, rough, glos	sy, heavy glossy, tough), tra	nsparencies, labels, envelo	pes, card stock	
Connectivity Interfaces	Bi-directional IEEE-1284-C		SB 2.0 port, two open EIO	slots, foreign interface for	interface for Bi-directional IEEE-1284-C parallel port, Hi-Speed USB 2.0 port, one open EIO slot, foreign				
		third party solutions, H	lost USB accessory port			harness, Host US	B accessory port		
Network connectivity			4.11	HP Jetdirect Fast Etherne	et embedded print server		D133 (
Fax interface			vailable PCL6, HP PCL5c, HP postsc	riet laval 3 amulation direct	Optional	Printer Management Langue	RJ-11 fax port		
Languages Fonts	93 internal TrueType fonts						•	n: additional foot solution	
Client operating systems		93 internal TrueType fonts scalable in HP PCL and HP postscript level 3 emulation; additional font solutions 80 internal TrueType fonts scalable in HP PCL and HP postscript level 3 emulation; available via flash memory XP* Home, XP* Professional, Server 2003; Mac OS 9.x and higher; Mac OS X Windows Vista* x66, Vista* x64, XP* x86, Windows* Server 2003 x86, Win							
3,7	10.1 or higher; optional: OS/2, UNIX [®] , HP OpenVMS						10.2, v10.3, v10.4 or later		
Network operating systems ¹²	Via the HP Jetdirect print server: XP® Home, XP® Professional, XP® 64-bit, Server 2003; Novell NetWare 3.2, 4.2, 5.x, 6.x (NDPS); Mac OS 8.6 or higher; Red Hat Linux 6.x, 7.x; SuSE Linux 6.x; HP-UX 10.20, 11.x; Solaris 2.5x, 2.6, 7, 8 (SPARC systems only); IBM AIX 3.2.5 or higher; MPE-iX; Citrix MetaFrame; Windows® Terminal Services; optional: OS/2, UNIX®, HP OpenVMS MICROSOft Windows® Vista® Compatible, Vista® Premium, XP®, Server 2003, XP®, ([Pv6 only supported on Windows® XP]; Novell 5.1 and later; Mac OS X v10.2, v10.3, v10.4 or later; SuSE Linux 8.x and later; HP-UX 10.20, 11.x; 11.; Solaris 2.5 and later; SuSE Linux 8.x and later; HP-UX 10.20, 11.x, 11.; Solaris 2.5 and later; MPE-iX; Citrix MetaFrame Server; Windows® 11.x, 11.5 or later; SuSE Linux 8.x and later; MPE-iX; Citrix MetaFrame Server; Windows® 12.x, 2.x, 2.x, 2.x, 2.x, 2.x, 2.x, 2.x,			y on Windows® 2003 a r; Red Hat Linux 7.x and SPARC systems only); IB					
Network protocols supported ¹²	party vendor: LPD, FTP, IP	PP), IPX/SPX, DLC/LLC, App	de; may require software fro oleTalk, Auto-IP, Apple Rend HCP, WINS, SNMP v 1, v 2	lezvous compatible, NDS,				CMPv6, Apple Bonjour ompatible, Telnet, SLP, OO, LPD, IP Direct Mode	
Dimensions (w by d by h)	20.5 x 23.5 x 22.9" (521 x 598 x 582 mm)	20.5 x 23.5 by 24.7" (521 x 598 x628.6 mm)	24.8 x 28.2 x 39.8" (630 x 715 x1010.6 mm)	24.8 x 28.2 x 54.2" (630 x 715 x 1375.5 mm)	31 x 25.	2 x 45.4" x 1153 mm)	43.5 x 25	5.2 x 45.4" 7 x 1153 mm)	
Weight	105.1lb (47.7 kg)	107.8lb (48.9 kg)	230lb (104.3 kg)	288lb (130.5 kg)		(124 kg)		(136 kg)	
What's in the box	on CD, in-box documento	ation: Getting Started Guid	ver, power cable, software e, full-capacity 11,000-pagi artridges ¹³ with HP ColorSp	e black and 10,000-page	drivers and docume 12,000-page black, cya	nernet embedded print servi entation on CD; in-box docu n, magenta, and yellow HP heet multipurpose tray: 500	mentation: Getting Started Color LaserJet print cartrid Sheet input trays 2, 3, 4;	Guide; full capacity ges ¹³ with HP ColorSphe	
				(700 lt 1 (000	toner; 100-s				
Also includes		4700n plus: Automatic two-sided printing accessory	4700dn plus: Printer stand	4700dtn plus: 40GB embedded hard drive, stapler/stacker with job offset	toner; 100-s	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide	CM4730f plus: 500-sheet stapler/stacker	CM4730fsk plus:	
Environmental ranges	0-11 500	4700n plus: Automatic two-sided printing accessory	4700dn plus: Printer stand	embedded hard drive, stapler/stacker with job offset		CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide	500-sheet stapler/stacker	CM4730fsk plus: 700-sheet, 3-bin maill	
Environmental ranges Power	Operating: 50°	4700n plus: Automatic two-sided printing accessory	4700dn plus: Printer stand	embedded hard drive, stapler/stacker with job offset		CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide	500-sheet stapler/stacker ecommended: 63° to 77° f	CM4730fsk plus: 700-sheet, 3-bin mail	
Environmental ranges Power Pressure (bystander)	Operating: 50°	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; re	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 %	embedded hard drive, stapler/stacker with job offset		CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 %	CM4730fsk plus: 700-sheet, 3-bin mail	
Environmental ranges Power Pressure (byslander) Altitude	Operating: 50°	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; re	4700dn plus: Printer stand	embedded hard drive, stapler/stacker with job offset		CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n	500-sheet stapler/stacker ecommended: 63° to 77° f	CM4730fsk plus: 700-sheet, 3-bin maill	
Environmental ranges Power Pressure (byslander) Altitude	Operating: 50°	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 %	embedded hard drive, stapler/stacker with job offset	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide ** to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m)	CM4730fsk plus: 700-sheet, 3-bin maill : (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power	Operating: 50°	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r 0 to 7500 ft Active: 6.7 B(A)	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m)	embedded hard drive, stapler/stacker with job offset	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau	CM4730fsk plus: 700-sheet, 3-bin maill (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander)		4700n plus: Automatic two sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r O to 7500 ft Active: 6.7 B(A) Active: 50 dB(A),	4700dn plus: Printer stand ccommended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) ; Ready: 7.7 B(A)	embedded hard drive, stapler/stacker with job offset F (17° to 25° C)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau	CM4730fsk plus: 700-sheet, 3-bin maill (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage**		4700n plus: Automatic two sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r O to 7500 ft Active: 6.7 B(A) Active: 50 dB(A),	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) ; Ready: 7.7 B(A) standby: 31 d(B)A	embedded hard drive, stapler/stacker with job offset F (17° to 25° C)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing, Ready: inau IB(A), printing; Ready: inau	CM4730fsk plus: 700-sheet, 3-bin maill (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage**		4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r 0 to 7500 ft Active: 6.7 B(A) Active: 50 dB(A),	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) ; Ready: 7.7 B(A) standby: 31 d(B)A	embedded hard drive, stapler/stacker with job offset F (17° to 25° C)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone card, Fax Install Guide to 86° F (15° to 30° C); r Operating: 10 to 70 %; r 0 to 8530 ft ve: 6.0 B(A), copying; 6.3 re: 52 dB(A), copying; 50 c 110 to 127 VAC (±109)	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing, Ready: inau IB(A), printing; Ready: inau	CM4730fsk plus: 700-sheet, 3-bin mailt (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage* Power consumption*	110 to 127 V (±	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r 0 to 7500 ft Active: 6.7 B(A) Active: 50 dB(A),	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) ; Ready: 7.7 B(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/	embedded hard drive, stopler/stacker with job offset F (17° to 25° C)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide 10 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ff ve: 6.8 B(A), copying; 6.3 re: 52 dB(A), copying; 50 c 110 to 127 VAC (±10°)	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing, Ready: inau B(A), printing; Ready: inau (6), 50/60 Hz (±2 Hz)	CM4730fsk plus: 700-sheet, 3-bin mailt (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage** Power consumption* Active, printing	110 to 127 V (±	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r 0 to 7500 ft Active: 6.7 B(A) Active: 50 dB(A),	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) ; Ready: 7.7 B(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/	embedded hard drive, stopler/stacker with job offset F (17° to 25° C)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft ve: 6.0 B(A), copying; 6.3 ve: 52 dB(A), copying; 50 c 110 to 127 VAC (±10°	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau B(A), printing; Ready: inau \$\(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\) \(\	CM4730fsk plus: 700-sheet, 3-bin mailt (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage* Power consumption* Active, printing Active, scanning	110 to 127 V (±	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r O to 7500 ft Active: 6.7 B(A) Active: 50 dB(A), £10%), 50/60 Hz (±2 Hz); wotts	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) ; Ready: 7.7 B(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/	embedded hard drive, stopler/stacker with job offset F (17° to 25° C)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; r 0 to 8530 ft ve: 6.0 B(A), copyring; 6.3 re: 52 dB(A), copyring; 50 c 110 to 127 VAC (±10:	500-sheet stapler/stacker ecommended: 63° to 77° F ecommended: 20 to 60 % (0 to 2600 m) D(A), printing; Ready: inau B(A), printing; Ready: inau S), 50/60 Hz (±2 Hz) watts watts	CM4730fsk plus: 700-sheet, 3-bin maill (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage** Power consumption* Active, printing Active, scanning Ready Standby PowerSave	110 to 127 V (±	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; n O to 7500 ft Active: 6.7 D(A) Active: 50 dB(A), 110%), 50/60 Hz (±2 Hz); watts	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % [0 to 2300 m] Ready: 7.7 D(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/ 591 watts 63 watts	embedded hard drive, stapler/stacker with job offset F (17° to 25° C) (60 Hz (±2 Hz)	Operating: 59	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n tve: 6.8 B(A), copyring; 6.3 ve: 52 dB(A), copyring; 50 c 110 to 127 VAC (±10°) 720 760 85 to	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau B(A), printing; Ready: inau \$\(\), 50/60 Hz (\pm 2 Hz) watts watts watts	CM4730fsk plus: 700-sheet, 3-bin maill (17° to 25° C)	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage* Power consumption* Active, printing Active, scanning Ready Standby	110 to 127 V (± 567 v 55 v	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r O to 7500 ft Active: 6.7 B(A) Active: 50 dB(A), £10%), 50/60 Hz (±2 Hz); watts vatts 0.3	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) Freedy: 7.7 B(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/ 591 watts	embedded hard drive, stopler/stacker with job offset F (17° to 25° C) (60 Hz (±2 Hz) 623 watts 66 watts	Operating: 59 Acti	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n tve: 6.8 B(A), copyring; 6.3 ve: 52 dB(A), copyring; 50 c 110 to 127 VAC (±10°) 720 760 85 to	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau (8), 50/60 Hz (±2 Hz) watts watts watts watts watts watts	CM4730fsk plus: 700-sheet, 3-bin mail (17° to 25° C) dible	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage ¹⁶ Power consumption ¹⁶ Active, printing Active, scanning Ready Standby PowerSave Off	110 to 127 V (± 567 v 55 v	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r O to 7500 ft Active: 6.7 B(A) Active: 50 dB(A), £10%), 50/60 Hz (±2 Hz); watts vatts 0.3	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) Ready: 7.7 B(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/ 591 watts 63 watts 18	embedded hard drive, stopler/stacker with job offset F (17° to 25° C) (60 Hz (±2 Hz) 623 watts 66 watts	Operating: 59 Acti	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft ve: 6.0 B(A), copyring; 6.3 ve: 52 dB(A), copyring; 50 c 110 to 127 VAC (±10° 720 760 85 s	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau (8), 50/60 Hz (±2 Hz) watts watts watts watts watts watts	CM4730fsk plus: 700-sheet, 3-bin mailt (17° to 25° C) dible	
Environmental ranges Power Pressure (byslander) Altitude Acoustics Power Pressure (byslander) Required input voltage " Power consumption" Active, printing Active, scanning Ready Standby PowerSave Off Typical Electricity Consumption (TEC)	110 to 127 V (± 567 v 555 v 17 v 6.522 kWh/Week- CISPR 22: 1997/EN ± 55024: 1998; F.C. little	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r Oto 7500 ft Active: 50 dB(A), Active: 50 dB(A), 4:10%), 50/60 Hz (±2 Hz); watts vatts vatts vatts 4/ CFR, Part 15 Class B; EN 14/ CFR, Part 15 Class B/18 89/336/EEC, the Low Vol	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) Ready: 7.7 B(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/ 591 watts 63 watts 18	embedded hard drive, stopler/stacker with job offset F (17° to 25° C) (60 Hz (±2 Hz) 623 watts 66 watts wetts p.com/go/energystar 61000-3-3: 1995; EN 1598, GB 17625. 1-1998;	7.731 kWh/Week-	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; r Oto 8530 ft ve: 6.0 B(A), copying; 6.3 re: 52 dB(A), copying; 50 c 110 to 127 VAC (±10° 720 760 85 to 0.42 -ENERGY STAR* qualified r EV 559 22:2006 Class A, I c ve 89/336/EEC and the Leve 80/36/EEC and the Leve 80/46/EEC and the Le	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing, Ready: inau B(A), printing; Ready: ina	CM4730fsk plus: 700-sheet, 3-bin maill (17° to 25° C) dible dible o.com/go/energystar	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage* Power consumption* Active, printing Active, scanning Ready Standby PowerSave Of If ypical Electricity Consumption (TEC)	110 to 127 V (± 567 v 55 v 77 v 6.522 kWh/Week- CISPR 22: 1997/EN 3 55024: 1998; F.C. little EMC Directive Argentina (TUV S Mark	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r 0 to 7500 ft Active: 6.7 B(A) Active: 50 dB(A), £10%), 50/60 Hz (±2 Hz); watts vatts vatts vatts 4/ CFR, Part 15 Class B; EN 4/ CFR, Part 15 Clas	4700dn plus: Printer stand commended: 62.6° to 77° ecommended: 30 to 70 % (0 to 2300 m) Franciscommended: 31 d(B)A 220 to 240 V (±10%), 50/ 591 watts 63 watts 63 watts 63 watts 63 watts 61000-3-2: 1995/A14; EN CES-403, Issue 3/GB9/254 tage Directive 73/23/EEC,	embedded hard drive, stopler/stacker with job offset F (17° to 25° C) (60 Hz (±2 Hz) 623 watts 66 watts wetts p.com/go/energystar 61000-3-3: 1995; EN 1598, GB 17625. 1-1998; and carries the Canada (cULCAN/CSA	7.731 kWh/Week- CISPR 22:2005 / 55024: 1998, FCC little 4.	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft ve: 6.8 B(A), copying; 6.3 *e: 52 dB(A), copying; 6.3 *e: 52 dB(A), copying; 50 o 110 to 127 VAC (±10° 720 760 85 v 26 v 27 v ENERGY STAR* qualified r CFR, Part 15 Class A, IC ve: 89/336/EEC and the L CEMarking CSA C22.2 No.60950-10	500-sheet stapler/stacker ecommended: 63° to 77° f ecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau B(A), printing; Ready: inau B(A), 50/60 Hz (±2 Hz) watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts watts	CM4730fsk plus: 700-sheet, 3-bin mail (17° to 25° C) dible dible a.com/go/energystar 1000.3-3:1995, EN 1998, GB1/625. //EEC and carries the	
Environmental ranges Power Pressure (bystander) Altitude Acoustics Power Pressure (bystander) Required input voltage** Power consumption* Active, printing Active, scanning Ready Standby PowerSave Off Typical Electricity Consumption (TEC) Power certifications EMC	110 to 127 V (± 567 v 55 v 17 v 6.522 kWh/Week- CISPR 22: 1997/EN 1 55024: 1998; FCC litle EMC Directive Argentina (TUV S Mark C22.2 No.60950-00), Ma	4700n plus: Automatic two-sided printing accessory to 86° F (10° to 30° C); re Operating: 10 to 80 %; r O to 7500 ft Active: 6.7 B(A) Active: 50 dB(A), £10%), 50/60 Hz (±2 Hz); watts vatts vatts 0.3 ENERGY STAR® qualified to 55022: 1998 Class B; EN- 4/ CFR, Part 15 Class B/II 89/336/EEC, the Low Voll CE-Marking cRs.92/98/Ds.1009/98), exico (NOM NYCENOM (Subchapter J for lasers); Not ar	4700dn plus: Printer stand 4700dn plus: Printer stand commended: 62.6° to 77° secommended: 30 to 70 % (0 to 2300 m) Freedy: 7.7 b(A) standby: 31 d(B)A 220 to 240 V (±10%), 50/ 591 watts 63 watts 63 watts watts 18 watts 19 yes A14; EN CES-003, Issue 3/GBY264 19 Directive 73/23/EEC, accordingly Australia (AS/NZ 3260), C	embedded hard drive, stopler/stacker with job offset F (17° to 25° C) (60 Hz (±2 Hz) 623 watts 66 watts 66 watts wetts p.com/go/energystar 61000-3-3: 1995; EN 1998, GB1/625. 1-1998; and carries the Canada (cULCAN/CSA 50; FDA-21 CFR Chapter 1	7.731 kWh/Week- CISPR 22:2005 / 55024: I998, FCC little 4. 1:2003, EMC Direct	CM4730 plus: HP LaserJet MFP Analog Fax Accessory 300, phone cord, Fax Install Guide * to 86° F (15° to 30° C); r Operating: 10 to 70 %; n 0 to 8530 ft ve: 6.8 B(A), copyring; 6.3 *e: 52 dB(A), copyring; 50 c 110 to 127 VAC (±10° 720 760 85 ; 26 · 0.42 -ENERGY STAR* qualified r EN 55022:2006 Class A, Ic V CFR, Part 15 Class A / IC ve 89/336/EEC and the Le CEMarking CSA C22.2 No.60950-1-0 Subchappter J for lassers). (1998; EG 201 121:1998, F	500-sheet stapler/stacker ecommended: 63° to 77° feecommended: 20 to 60 % (0 to 2600 m) B(A), printing; Ready: inau B(A), printing; Ready: inau B(A), 50/60 Hz (±2 Hz) watts watts watts watts watts models; see: http://www.hg EN 61000-3-2:2000, EN 6 ES-003, Issue 4 / GBY254 ov Voltage 14 / GBY254 accordingly 3), USA (ULUL 60950-1; FiClass 1 Laser/LED Product.	CM4730fsk plus: 700-sheet, 3-bin mail (17° to 25° C) dible dible c.com/go/energystar 1000-3-3:1995, EN 1998, GB1/62'b. //EEC and carries the DA-21 CFR Chapter 1	

⁹ Exact speed varies depending on the system configuration, software application, driver, and document complexity.

10 Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

11 HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

12 Not all protocol and operating system combinations are supported. For more information, go to: www.hp.com/support/et_printing.

13 All print cartridge page yields are based at the percent page coverage. Declared yield value in accordance with ISO/IEC 19752. For more information, visit www.hp.com/go/pageyield.

14 Values subject to change. See www.lp.com/support/cl/4700 or www.lp.com/support/cl/4730 for current information. Power reported is the highest value measured using all standard valuages.

Ordering information

	HP Color LaserJet 4700 series printer		HP Color LaserJet CM4730 MFP series	
Printer	 HP Color LaserJet 4700n printer HP Color LaserJet 4700dn printer HP Color LaserJet 4700dtn printer HP Color LaserJet 4700ph+ printer 	Q7492A Q7493A Q7494A Q7495A	 HP Color LaserJet CM4730 MFP HP Color LaserJet CM4730f MFP HP Color LaserJet 4700fsk MFP HP Color LaserJet 4700fm MFP 	CB480A CB481A CB482A CB483A
Accessories	 500-sheet paper input feeder 750-sheet stapler/stacker with job offset¹⁵ Printer stand 	Q7499A Q7003A Q7501A	 500-sheet paper input feeder 750-sheet, 3-bin mailbox HP LaserJet MFP Analog Fax Accessory 300 HP Digital Sending Software 4 HP AutoStore 	Q7521A Q7523A Q3701A T1936AA T1943AA
HP Color LaserJet Print Cartridge with HP Colorsphere Toner [™]	 Black Print Cartridge (11,000 pages) Cyan Print Cartridge (10,000 pages) Yellow Print Cartridge (10,000 pages) Magenta Print Cartridge (10,000 pages) 	Q5950A Q5951A Q5952A Q5953A	 Black Print Cartridge (12,000 pages) Cyan Print Cartridge (12,000 pages) Yellow Print Cartridge (12,000 pages) Magenta Print Cartridge (12,000 pages) 	Q6460A Q6461A Q6462A Q6463A
Connectivity accessories	 HP Jetdirect 625n Gigabit Ethernet Internal Print Server HP Jetdirect 635n IPv6/IPsec and Gigabit Ethernet Internal Print Server HP Jetdirect ew2400 802.11g Wireless & Fast Ethernet External Print Server 	J7960G J7961G J7951G	 HP Jetdirect en1700 USB 2.0 Print Server HP Jetdirect en3700 USB 2.0 Print Server (print only) HP Jetdirect ew2400 Wireless USB 2.0 Print Server (print only) HP Jetdirect 510x Parallel Print Server 	J7988G J7942G J7951G J7983G
	(USB Hi-Speed) • HP Jetdirect en3700 Fast Ethernet External Print Server (USB Hi-Speed) • HP bt1300 Bluetooth® Wireless Printer Adapter	J7942G J6072G	 (print only) HP Jetdirect 300x Parallel Print Server (print only) HP Jetdirect 635n EIO Print Server HP Jetdirect 630n EIO Print Server 	J3263G J7961G J7997G
Memory and storage	 20GB HP high-performance EIO hard disk 128MB 200-Pin DDR DIMM 256MB 200-Pin DDR DIMM 512MB 200-Pin DDR DIMM 	J6073A Q7721A Q7722A Q7723A	 128MB 200-Pin DDR DIMM 256MB 200-Pin DDR DIMM 512MB 200-Pin DDR DIMM 	Q7721A Q7722A Q7723A
Cables	 Parallel cable, 3-meter IEEE 1284 A-C Parallel cable, 10-meter IEEE 1284 A-C HP USB cable, 1.83-meter (A-C) 	C2946A C2947A C6518A	 Parallel cable, 3-meter IEEE 1284 A-C Parallel cable, 10-meter IEEE 1284 A-C 	C2946A C2947A
Supplies	 Staple cartridge (5,000 staples) for stapler/stacker with job offset 110 volt image fuser 220 volt image fuser 110 volt image transfer kit 	C8091A Q7502A Q7503A Q7504A	 Staple cartridge (5,000 staples) for stapler/stacker ADF replacement Mylar sheets ADF maintenance kit 110 volt image fuser 220 volt image fuser 110 volt image transfer kit 	C8091A Q6496A Q5997A Q7502A Q7503A Q7504A
Service and support	 3-year warranty service, 4-hour response, standard business hours (9x5) 3-year next business day response Networked hardware installation and configuration 	U3795E H3113E H2872E	 3-year, warranty service, 4-hour response, standard business hours (9x5) 3-year, warranty service, 4-hour response, extended business hours (13x5) 3-year, next business day response Networked hardware installation and configuration 	HC116E HC119E HC113E U2010E
Paper	 North America: www.hp.com/go/everydaypapers Contact HP via phone: USA: 1-800-477-5010 		North America: www.hp.com/go/everydaypapers Contact HP via phone: 1-800-477-5010	
Third-party solutions	• www.hp.com/go/gsc		• www.hp.com/go/gsc	

¹⁵ Compatible with HP Color LaserJet 4700dn, 4700dtn, and 4700ph+ printer models only.

¹⁶ All print cartridge page yields are based at five percent page coverage. Declared yield value in accordance with ISO/IEC 19752. For more information, visit www.hp.com/go/pageyield.









© Copyright 2005-2007 Hewlett-Packard Development Company, L.F

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

The Bluetooth trademarks are owned by its proprietor and used by Hewlett-Packard Company under license. ENERGY STAR and the ENERGY STAR logo are registered U.S marks. Linux is a U.S. registered trademark of Linus Torvalds. Microsoft, Windows, Windows NT and Windows XP are registered trademarks of Microsoft Corporation. RED HAT READY™ Logo and RED HAT CERTIFIED PARTINER™ Logo are trademarks of Red Hat, Inc. Microsoft, Windows, and Windows XP are U.S. registered trademarks of Microsoft Corporation. UNIX is a registered trademark of The Open Group. Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Printed in U.S.A.

For more information visit our website at www.hp.com

4AA1-1150ENUC, Rev 4, July 2007

